

BAUDOQUIN 150-165 kVA

Technical Specifications



ENGINE

- BAUDOQUIN series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged & air to air charge cooled
- Direct injection
- Electronic governor system
- 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

QUALITY STANDARD

Our gen-sets; VDE 0530, BS 4999, BS 5000, IEC 34, TS ISO 8528, TS EN 12601 are manufactured in accordance with the standards mentioned above. Our company fulfills ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 management system requirements, and have the accredited certificates of Kiwa & MEYER. Also we've GOST-R certificate. Our gen-sets have TS ISO 8528-5, TS EN 12601 product standard certificates.

Our gen-sets are CE certified in accordance with the requirements of 2000/14/EC, noise emission directive.

ALTERNATOR

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure

EXTRA EQUIPMENTS

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter

CANOPY

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

AUTOMATIC CONTROL PANEL

- LCD display screen
- Battery charger
- Hardware and materials needed
- USB port & RS-485 output

GEN-SET SAFETY PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start/stop failure



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender



BAUDOIN Series

Diesel Generator Sets

BAUDOIN Series Diesel Generator Sets 150-165 KVA

MODEL				E BD XX 0150	E BD XX 0165
GROUP	GEN - SET POWER	STAND BY	KVA	150	165
			KW	120	132
		PRIME	KVA	136	150
			KW	109	120
	CANOPY DIMENSION (W x L x H) mm			1050 x 3580 x 1870	1050 x 3580 x 1870
	CANOPY WEIGHT kg			1810	1950
	OPEN DIMENSION (W x L x H) mm			1050 x 3100 x 1650	1050 x 3100 x 1650
	OPEN WEIGHT kg			1560	1700
ENGINE	BRAND			BAUDOIN	BAUDOIN
	TYPE			6M11G150/5e2	6M11G165/5e2
	POWER	STAND BY	KW	140	152
		PRIME	KW	128	138
	SPEED (rpm)			1500	1500
	CYCLE			4	4
	DISPLACEMENT (lt)			6,75	6,75
	NUMBER OF CYLINDERS			6 IN LINE	6 IN LINE
	BORE AND STROKE (mm x mm)			105 x 130	105 x 130
	COMPRESSION RATIO			18:1	18:1
	GOVERNOR TYPE			ELECTRONIC	
	INDUCTION			TURBOCHARGED - AIR TO AIR CHARGE COOLED	
	COMBUSTION SYSTEM			DIRECT INJECTION	
	COOLING SYSTEM			WATER	
	FUEL CONSUMPTION (lt/h)	100% OF PRIME POWER		30,4	32,7
		75% OF PRIME POWER		23,1	24,5
50% OF PRIME POWER		15,9	16,7		
TOTAL LUBRICATION SYSTEM CAPACITY (lt)			16	16	
TOTAL COOLANT CAPACITY (lt)			28	28	
FUEL TANK CAPACITY (lt)			380	380	

Emsa reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

