

PERKINS 400-550 kVA

Technical Specifications



ENGINE

- PERKINS series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged & air to air charge cooled
- Direct injection
- Electronic governor system
- 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

QUALITY STANDARD

Our gen-sets; VDE 0530, BS 4999, BS 5000, IEC 34, TS ISO 8528, TS EN 12601 are manufactured in accordance with the standards mentioned above. Our company fulfills ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 management system requirements, and have the accredited certificates of Kiwa & MEYER. Also we've GOST-R certificate. Our gen-sets have TS ISO 8528-5, TS EN 12601 product standard certificates.

Our gen-sets are CE certified in accordance with the requirements of 2000/14/EC, noise emission directive.

ALTERNATOR

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure

EXTRA EQUIPMENTS

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-6 gensets
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter

CANOPY

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

AUTOMATIC CONTROL PANEL

- LCD display screen
- Battery charger
- Hardware and materials needed
- USB port & RS-485 output

GEN-SET SAFETY PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start/stop failure



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender



PERKINS Series Diesel Generator Sets 400-550 kVA

MODEL				E PR XX 0400	E PR XX 0450	E PR XX 0500	E PR XX 0550
GROUP	GEN - SET POWER	STAND BY	kVA	400	450	500	550
			kW	320	360	400	440
		PRIME	kVA	350	400	455	500
			kW	280	320	364	400
	CANOPY DIMENSION (W x L x H) mm			1500 x 4400 x 2665	1500 x 4400 x 2665	1500 x 4400 x 2665	1500 x 4400 x 2665
	CANOPY WEIGHT kg			3900	4100	4200	4200
	OPEN DIMENSION (W x L x H) mm			1500 x 3785 x 2020	1500 x 3785 x 2020	1500 x 3785 x 2020	1500 x 3785 x 2020
	OPEN WEIGHT kg			3200	3400	3500	3500
ENGINE	BRAND			PERKINS	PERKINS	PERKINS	PERKINS
	TYPE			2206C - E13TAG2	2206C - E13TAG3	2506C - E15TAG1	2506C - E15TAG2
	POWER	STAND BY	kW	349	392	435	478
		PRIME	kW	305	349	396	435
	SPEED (rpm)			1500	1500	1500	1500
	CYCLE			4	4	4	4
	DISPLACEMENT (lt)			12,5	12,5	15,2	15,2
	NUMBER OF CYLINDERS			6 IN LINE	6 IN LINE	6 IN LINE	6 IN LINE
	BORE AND STROKE (mm x mm)			130 x 157	130 x 157	137 x 171	137 x 171
	COMPRESSION RATIO			16,3 : 1	16,3 : 1	16,0:1	16,0:1
	GOVERNOR TYPE			ELECTRONIC			
	INDUCTION			TURBOCHARGED - AIR TO AIR CHARGE COOLED			
	COMBUSTION SYSTEM			DIRECT INJECTION			
	COOLING SYSTEM			WATER			
	FUEL CONSUMPTION (lt/h)	100% OF PRIME POWER		75,00	85,00	99,00	106,00
		75% OF PRIME POWER		58,00	65,00	73,00	81,00
50% OF PRIME POWER		40,00	46,00	51,00	55,00		
TOTAL LUBRICATION SYSTEM CAPACITY (lt)			40	40	62	62	
TOTAL COOLANT CAPACITY (lt)			51,40	51,40	58	58	
FUEL TANK CAPACITY (lt)			970	970	970	970	

Emsa reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.